



# INSULATION TAPE

IDH 908974, 908977, 908978, 908979, 908980, 908981, 908982

October 2015

## DESCRIPTION

Sellotape® Insulation Tape is made of a plasticised and stabilised soft Polyvinyl Chloride (PVC) backing with a strong natural rubber adhesive. Is flexible and will conform to most irregular surfaces. The non-corrosive, pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts for application. It is suitable for uses under 600V or 80°C.

## SPECIFICATIONS

<b>Total Thickness:</b>	180 micron
<b>Tensile Strength:</b>	2.6 kg per 10 mm width
<b>Elongation (% at Break):</b>	200
<b>Adhesion to Steel:</b>	0.13 kg per 10 mm width
<b>Dielectric at Break:</b>	1,000 Volts / mil
<b>Adhesion to Backing:</b>	0.13 kg / 10 mm width
<b>Flame Retardant:</b>	No Fail
<b>Colours:</b>	Black, Red, Green, Blue, White, Yellow

## APPLICATIONS

- Connection or splicing of electric wires, cables and cords for electrical insulation
- Insulation and protection of wires in electrical appliances and machines
- Applications where cold resistant materials are required
- As a grip for hand tools
- Repairing or mending of plastic products
- Wherever you need strong dependable holding, reinforcing or insulation

*The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.*

*The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.*

