



PREMIUM PACKAGING TAPE

IDH 1996855, 1996854, 908895, 908891, 908892, 908893, 908894

October 2015

DESCRIPTION

Sellotape® Premium Packaging Tape is a heavy duty, bi-axially oriented polypropylene film with an aggressive rubber adhesive. These tapes have a high tensile strength, high impact resistance, are flexible and conform well to irregular surfaces.

Sellotape® Premium Packaging Tapes have a high resistance to water, acids, alkalis and most solvents. Sellotape® Premium Packaging Tapes have minimal static and good handling characteristics.

SPECIFICATIONS

Backing:	Polypropylene film
Total Thickness:	50 micron
Film Thickness:	28 micron
Peel Adhesion:	>450 g per 25mm width
Tensile Strength:	>8 kg per 25mm width
Elongation:	>80%

APPLICATIONS

- General packaging applications
- Sealing parcels
- "U" sealing the top and bottom of cartons
- Suitable for hand dispensers
- Suitable for heavy parcels

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.

